



Husqvarna TS 114

Purposely engineered for ease of use, this reliable garden tractor delivers an exceptional mowing experience on any large lawn – even in narrow passages. Achieve excellent results without straining your body thanks to its ergonomically placed levers, side-by-side pedals and spring-assisted cutting deck. Conveniently compact for optimised storage, maintenance and operation, enjoy trouble-free ownership and a perfectly cut lawn.



Adjustable driver seat

Tool-free adjustment of seat position to quickly set a comfortable driving position.



Hour meter

Hour meter for easy control of operating time and service and maintenance intervals.

Dual headlights

Dual headlights at the front for clear visibility when driving in dark conditions.



Side discharge cutting deck

Equipped with a 95cm side discharge cutting deck.



FEATURES

- Dual headlights at the front for clear visibility when driving in dark conditions.
- Hour meter for easy control of operating time and service and maintenance intervals.
- Tool-free adjustment of seat position to quickly set a comfortable driving position.
- Equipped with a 95cm side discharge cutting deck.
- Comfortable driving position and operation thanks to the adjustable seat and easy-access controls.
- The cutting deck is equipped with anti-scalp wheels, which reduce the risk of scalping when cutting uneven lawns.
- Compact design for effortless navigation in narrow passages and easy storage while not in use.
- ROS is activated with the start key for quick access to reverse mowing, and to minimise the risk of the function being used unintentionally.
- Fuel level window makes it easy to check the fuel level.
- Dual pedal drive for better drive control and easy, intuitive operation.
- Additional functionality thanks to the included towing hook which enables the use of many accessories.
- Control levers on only one side make it easy to get in and out of the seat on the other side.
- Easy engagement of cutting blades; simply pull the switch on the control panel.
- Easy to get operating under any weather condition and no choking needed. Just turn the key and go.
- Easy speed and direction control with pedal-operated hydrostatic transmission.
- Easily accessible cutting height adjustment for improved ergonomics.

Technical Specifications	
BATTERY	
Battery capacity	20 Ah
Battery voltage	12 V
CAPACITY	
Net power at preset rpm	2800 rpm
Power output	9.0 kW
DIMENSIONS	
Article gross weight	209000 g
Article net weight	169000 g
Base machine, height	110 cm
Base machine, length	166.5 cm
Base machine, width (chute down)	119 cm
Base machine, width	92 cm
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Lever, while seated
Cutting height steps	6
Cutting width	95 cm
Height	110 cm
Seat back height	Medium
Tyre dimensions, front	15x6-6
Tyre dimensions, rear	18x8.5-8
Weight (complete product w/o side packed articles)	184 kg
Wheelbase	115 cm
ENGINE	
Cylinders	1
Cylinder displacement	452 cm ³
Engine brand	Husqvarna
Engine cooling	Air
Engine name	HS 452AE
Fuel tank volume	6 l
Fuel tank volume	1.59 gal (US)
Generator	12 A
Motor/engine manufacturer	Husqvarna
Motor/engine model	HS 452AE
Transmission manufacturer	Hydro-Gear
Transmission model	T2
Transmission type	Hydrostatic
EQUIPMENT	
Air filter type	Cartridge with pre filter
Anti-scalp wheels	2
BioClip® kit	Available as accessory
Blade engagement	Electric clutch
Blade type	Discharge
Blades	2 pcs
Collector	Available as accessory
Cup holder	Yes
Cutting deck type	Stamped
Cutting methods	Collection/BioClip®/Side discharge
Deck Wash Port	Yes
Deflector	No
Drive method	Dual pedal-operation
Front-End Protection	Available as accessory

Technical Specifications

Generator	12 A
Greasable mandrels	No
Headlights	Yes
Hour meter type	Digital
Mulching kit	Available as accessory
Powder-coated cutting deck	No
Seat type	Standard
LUBRICANTS	
Engine lubrication type	Pressure with Oilfilter
Fuel consumption	412 g/kWh
Fuel tank location	Front
Oil capacity	1.2 l
Oil filter	Yes
Power/fuel type	Petrol
MATERIALS	
Cutting deck material	Steel
Master pack: Paper + Cardboard	0 g
Metal total	3820 g
Paper + Cardboard total	7410 g
PE total	336.7 g
PET total	0 g
Plastic foil	336.7 g
Plastic rigid	0 g
Plastic total	336.7 g
PS/EPS/HIPS total	0 g
Seat material	PU
PACKAGING	
Packaging height	850 mm
Packaging length	1700 mm
Packaging volume	1640 dm ³
Packaging width	1135 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	97.6 dB(A)
Sound pressure level at operators ear	83.4 dB(A)
VIBRATIONS	
Vibration level seat	2.0 m/s ²
Vibration level steering wheel	5.6 m/s ²