



Husqvarna TS 218T

Husqvarna TS 218T garden tractor combines a convenient ride with efficient cutting and a powerful engine to maintain larger lawns easily. Easy-to-reach controls and levers, quickly adjusted seat contribute to high comfort and good ergonomics. Small equipment and hand tools can be stored in practical storage compartments to be easily accessible when needed. The 108 cm cutting deck offers excellent cutting performance and with a wide range of cutting heights, adjustments can be made to suit different needs and grass conditions. The adjustment is spring assisted to reduce strain for operator. Engine features like auto choke, oil filter and twin cylinder, and robust design with cast iron front axles ensure reliable and durable performance. ROS (reverse operation system) is activated with the start key for quick access to reverse mowing, and to minimise the risk of the function being used unintentionally. There is also a brush guard to protect the front.



Ergonomic controls

All controls are ergonomically placed and easy to reach from the driver's seat. It provides high comfort and minimises the effort, especially during long working periods.



Turn key start

Easy to get operating under any weather condition and no choking needed. Just turn the key and go.



One open storage compartment on the left and one at the back with a lid for easy access to equipment during mowing.



Easy refueling

Thanks to the external fuel cap, you don't have to open the engine hood when refueling.



FEATURES

- One open storage compartment on the left and one at the back with Easily accessible cutting height adjustment for improved a lid for easy access to equipment during mowing.
- Easy to get operating under any weather condition and no choking needed. Just turn the key and go.
- All controls are ergonomically located and easy to reach from the operator's seat.
- Thanks to the external fuel cap, you don't have to open the engine hood when refueling.
- Equipped with LED headlights for higher visibility from the driver's position when operating in dark conditions.
- Dual pedal drive for better drive control and easy, intuitive operation.

- ergonomics.
- Easy engagement of cutting blades; simply pull the switch on the control panel.
- The driver's seat can be easily adjusted by sliding it to the desired position without you having to get off the product.
- Robust design with cast iron front axles for reliable and durable performance.
- ROS is activated with the start key for quick access to reverse mowing, and to minimise the risk of the function being used unintentionally.
- Bumper for protecting the front

Technical Specifications	
BATTERY	
Battery capacity	24 Ah
Battery voltage	12 V
CAPACITY	
Net power at preset rpm	3100 rpm
Turning radius, min	12.4 in
Uncut circle	31.5 cm
DIMENSIONS	01.0 dii
Article gross weight	282740 g
Article gross weight Article net weight	235000 g
Base machine, height	112.4 cm
Base machine, length	202.9 cm
Base machine, length Base machine, width	137.5 cm
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Lever, while seated
Cutting height steps	10
Cutting width	108 cm
Height	112.4 cm
Seat back height	Medium
Tyre dimensions, front	15x6-6
Tyre dimensions, nonc	20x10-8
Tyre size, rear Diameter	20x10 6
Tyre size, rear Width	10 in
Wheel/rim size, front Diameter	6 in
Wheel/rim size, rear Diameter	8 in
Wheelbase	125 cm
ENGINE	123 (11)
	2
Cylinders Cylinders	2
Cylinder displacement	708 cm ³
Engine brand	Husqvarna
Engine cooling	Air HV 708AE
Engine name	13 I
Fuel tank volume	
Fuel tank volume	3.43 gal (US)
Motor/engine manufacturer	Husqvarna HV 708AE
Motor/engine model Transmission manufacturer	Tuff Torq
	K46
Transmission model Transmission	
Transmission type	Hydrostatic
EQUIPMENT	
Air filter type	Cartridge with pre filter
Anti-scalp wheels	2
BioClip® kit	Available as accessory
Blade engagement	Electric clutch
Blade type	Discharge
Blades	2 pcs
Collector	Available as accessory
Cup holder	Yes
Cutting deck type	Stamped (St. 2) a (St. 4) a
Cutting methods	Collection/BioClip®/Side discharge
Deck lifting system	Manual, hand operated
Deck Wash Port	Yes
Deflector	No
Drive method	Dual pedal-operation
Electric start	Yes
Front-End Protection	Brush Guard Style Bumper
Greasable mandrels Headlights	No Yes

Technical Specifications	
Hour meter type	Digital
Mulching kit	Available as accessory
Powder-coated cutting deck	No
Seat type	Comfort
LUBRICANTS	
Engine lubrication type	Pressure with Oilfilter
Fuel tank location	Front
Oil capacity	2.41
Oil filter	Yes
Power/fuel type	Petrol
MATERIALS	
Cutting deck material	Steel
Master pack: Paper material	0 g
Metal total	O g
Paper material total	11140 g
HDPE (02) total	0 g
PET (01) total	Og
Plastic foil total	0 g
Plastic rigid total	0 g
Plastic total	0 g
PS/EPS/HIPS (06) total	Og
Seat material Seat material	PU