

525iLK Combi Trimmer

Product no: 970 55 16-02

Husqvarna 525iLK is a robust, high-performance professional battery combi machine. Well-balanced, lightweight and power-equivalent to a 25 cc petrol machine. This battery combi machine is designed for full-time use, delivering the performance you need with a brushless E-TORQ motor and grass trimmer attachment with 42 cm cutting diameter. The wide range of Husqvarna combi attachments makes it a highly versatile tool for grass cutting, pruning, hedge trimming, edging or cleaning. Integrated connectivity for easy connection to digital services.



Flexible BLi Battery System

Our BLi battery system allows flexible use in different Husqvarna tools. You will always find a tailored battery solution that perfectly suits your task at hand.



Multi Purpose

Multi-purpose machine with several attachments available as accessories.



Integrated Connectivity

Built-in connectivity module can easily be connected to Husqvarna Fleet Services™. Allowing you to see each machine's last known location, its usage stats and service history – and much more.



ActiveCool

ActiveCool enables efficient cooling of the battery, both during charging and discharging. Thanks to the active cooling system your battery powered product remains fully productive.



Battery through Body Design

Smart battery pack position, placed horizontally through the body of the machine. Reduces the risk of having dirt, chips, dust and water accumulate in the battery compartment, causing connector issues.



Optimised Shaft & Gear

Optimised shaft length and 35° bevel gear facilitates operation and allows the cutting equipment working parallel to the ground.

525iLK Combi Trimmer

Product no: 970 55 16-02

Technical Specifications

BATTERY

Battery charger	Not included
Number of batteries included	0
Weight (excl. battery and cutting equipment)	3.3 kg

CAPACITY

Maximum power speed	8400 rpm
Maximum rpm output shaft	5800 rpm
Output shaft thread	M10x1.25 Lefthanded

DIMENSIONS

Article gross weight	5000 g
Article net weight	3000 g
Cutting width	42 cm
Tube length	1436 mm
Tube diameter	24 mm

ENGINE

Motor type	BLDC (brushless)
------------	------------------

EQUIPMENT

Connected digital function set (calc)	Husqvarna Common Service Tool : N/A N/APremium : N/A N/ACconnectivity BT : N/A N/A
Drive gear angle	30°
Gear ratio	1
Handle type	Loop
Trimmer head	T35 M10
Output shaft thread	M10x1.25 Lefthanded

PACKAGING

Packaging height	170 mm
Packaging length	920 mm
Packaging width	170 mm
Quantity in Master pack	1

MATERIALS

Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g

SOUND AND NOISE

Sound power level, guaranteed (LWA)	95 dB(A)
Sound power level, measured	93 dB(A)
Sound pressure level at operators ear	86 dB(A)

VIBRATIONS

Daily Vibration (Aeqv)	1.5 m/s ²
Equivalent vibration level (ahv, eq) front handle	1.4 m/s ²
Equivalent vibration level (ahv, eq) rear handle	1.5 m/s ²